

## WHARFEDALE PRO R1604 Mixer Passivo



Produttore : Wharfedale Pro  
Cod.Art. : 10187

### MIXER PASSIVO

La serie R di mixer Wharfedale Professional è progettata per offrire una qualità audio superiore in un sistema facile da usare, e di grande valore. La qualità delle serie R è tale che può essere utilizzato in una varietà di applicazioni professionali.

#### Caratteristiche principali

- 4 ingressi mono
- 4 ingressi mic
- 4 ingressi stereo con tripla banda di equalizzazione - 2 uscite master
- 2 uscite alt
- 1 uscita monitor
- 1 uscita cuffia
- 1 uscita rec - 2 mandate ausiliarie - alimentazione phantom a 48v - kit per il montaggio a rack 19" in dotazione

#### Specifiche tecniche

- Hum and noise: -127db equivalent input noise
- (average,rs=150): -95db residual noise (mix I / r,alt 3~4,aux send 1~2,ctrl room), Master fader at nominal level and all channel assign switch off
- Dimensions (hxwxd): 80.3 x 307 x 389 mm
- Weight:
- 5.9kg
- 13.0 lbs
- Maximum output level: +22db(mix I / r,alt 3~4) @600 ohm
- (0.5% t.h.d at 1khz): +22db(aux send1~2) @600 ohm, +22db(insert) @40k ohm, +22db(ctrl room) @600 ohm, Over 100mw (headphone) @40 ohm

## WHARFEDALE PRO R1604 Mixer Passivo

- Master Eq: turnover / rollover frequency: located 3db below the point of maximum amplification and attenuation
- Hi Eq: (+ / -15db) 12khz shelving
- Mid Eq: (+ / -15db) 2.5khz shelving
- Low Eq: (+ / - 15db) 80hz shelving
- Power consumption AC 100v / 120v / 230v / 240v, 50~60hz
- Total harmonic distortion (thd): 0.0025% @+14db 20hz~20khz
- (mix l / r, alt 3~4, aux send 1~2, ctrl room) @600 ohm
- Maximum levels:
  - Mic in: +4dBu
  - Tape in: +13dBu
  - All other inputs: +25dBu
  - Maximum voltage gain: 72db mic in to mix l / r, alt 3~4, 72db mic in to aux 1, 72db mic in to aux 2(post), efx, 74db mic in to control room l / r, 72db mic in to rec l / r, 54db line in to mix l / r, alt 3~4, 58db line in to aux 1, 58db line in to aux 2(post), 60db line in to control room l / r, 22db st in to mix l / r, alt 3~4, 20db aux return l / r in to mix l / r, 16db tape in to mix l / r,
- Interference (crosstalk) at 1khz:
  - Main Fader Down: -85dBu
  - Channel Alt / Mute Switch Engaged: -80dBu
  - Channel Fader Down: -70dBu
  - Mono input channel gain: 50dB variable (-60dB~-10dB), (-40dB~+10dB)
  - Peak indicator: Input Channel: Turns on 3dB Under Pre-fader Signal Clip
  - Level meters: 10-Segment LED x2 (Output of +4dB at 0dB) Main L / R
  - Phantom power: 48V DC

Prezzo : €209,00 IVA inclusa (~~€171,31 esclusa IVA~~)

Prezzo in offerta : €169,00 IVA inclusa (€138,52 esclusa IVA)