

ALTO Orient Express 400S



Cod.Art. : 10269

SISTEMA AUDIO PORTATILE CON MP3 PLAYER

L'OEX 400S è un sistema di amplificazione completo, compatto e versatile, che comprende un mixer con effetti DSP integrati e 2 diffusori L & R full range. Sono inoltre inclusi gli accessori essenziali come il cavo di alimentazione e i cavi di segnale. Al fine di garantire un'elevata trasportabilità, chiuso il sistema diventa un unico blocco, solido e dotato di trolley. Sull'OEX-400S è stato integrato un comodissimo lettore MP3 con ampio display, che lo rende perfetto per ogni tipologia di utilizzo, dalla conferenza al party.

Specifiche
tecniche

Mixer Section:

- Microphone / Line Input
- Frequency Response: 20Hz to 22 kHz +/-2dB
- Microphone Input Impedance: 3.9 kΩ;
- Line Input Impedance: 10 kΩ;
- Microphone Input S/N ratio: >100 dBu
- Microphone Inputs: Electronically Balanced - Discrete Input Configuration
- Line Inputs: Electronically Balanced
- Inputs Distortion (THD&N): 0.02% At 1 kHz
- Channel EQ: High shelving +/-15dB @12 kHz - Low shelving +/-15dB @80 kHz
- Aux Send: 1 with paths for DSP internal section, external DSP section and Monitor Out
- DSP Section: 24-bit HALL, ROOM, VOCAL, PLATE, STEREO DELAY, REV + DELAY, and REV+CHORUS combinations

ALTO Orient Express 400S

- Master Section: Master Level knob, 4 LEDs level meter DSP
Return level

Speakers Section:

- System Type: 2-way Coax Vented Box
- Frequency Response: 65Hz-20kHz @-10dB
- Spherical Horn Coverage: 70H° X 70V°
- Continuous Power: 150W AES Standard (each speaker)
- Peak Power: 300W Peak (each speaker)
- Protection: Electronic circuit on driver
- Speaker specifications: 10"(254mm) Low Frequency Driver - 2"(50.8mm) Voice Coil - 1"(25.4mm) Neodymium High
- Input connectors: Power Input with mono Jack

Amplifier Section:

- Power Continuous 1kHz, THD 1%: 2 x 200W @ 4Ω; 2 x 110W @ 8Ω;
- POWER EIAJ 1KHz, THD 1%: 2 x 250W @ 4Ω; 2 x 130W @ 8Ω;

MP3 Section

- USB HOST: Builds in the USB FULL speed (12Mbps) HOST control function, Supports the USB mass storage class
- FAT analysis: Supports FAT 16 and FAT 32, Supports VFAT (long file name), Supports multi-partion up to 1
- MP3 DECODE: Supports sample rates 8kHz, 32kHz, 11.025kHz, 22.05kHz, 44.1kHz, 12kHz, 24kHz, and 48kHz. Supports bit rate 8 to 320 kbps and VBR (Variable Bi Rate) except free format

Electric Specification:

- Frequency Response 20Hz~20kHz
- Output level: 0dB, S/N Ratio: >90dB
- Distortion (at 1kHz): <0.05%

NOTE: Sono inclusi 2 cavi per gli speaker e 2 microfoni AM6. I supporti non sono inclusi.

Prezzo : €479,00 IVA inclusa (€392,62 esclusa IVA)