

## TC ELECTRONIC BH500



Produttore : TC Electronic

Cod.Art. : 10430

TESTATA PER BASSO 500W

BH500 è il nome dell'ultima aggiunta tra gli amplificatori TC Electronic dell'era 2.0, una testata per basso che combinata ai cabinet BC212, BC210 o BC410 crea diverse soluzioni stack per adattarsi a concerti che vanno dai piccoli locali fino ai grandi ambienti. BH500 ospita le funzioni TubeTone e SpectraComp, già viste in altri modelli TC Electronic. TubeTone replica il comportamento delle sezioni pre e finale di un ampli valvolare, rendendo il suono un po' più caldo e raggiungendo il classico punch necessario nel rock, ad esempio. SpectraComp è un compressore adattivo che assicura al suono di basso di uscire bene dal mix sia che si suonino con le dita, con il plettro o slap. A completare la panoramica si aggiungono le 3 memorie digitali che permettono all'utente di cambiare il proprio suono all'istante e l'accordatore integrato.

Specifiche

Tecniche

INPUT SECTION

- Input connector: 1/4" jack
- Input impedance: 1 MOhm / 100 pF
- Gain range: -96 to 36dB

CONTROLLI DEL TONO

- Bass: Center Freq: 100Hz (Gain: +15/-24dB)
- Low Mid: Center Freq: 335Hz (Gain: +15/-24dB)
- High Mid: Center Freq: 900Hz (Gain: +15/-24dB)
- Treble: Center Freq: 1600Hz @ Gain: -24 to 0dB; 4000Hz @ Gain 0 to +15dB

- Tweeter Tone: 0 to 10, L-PAD Cabinet Recreation

- Tube Tone: 0 to 10, Tube amp Recreation

ALTRO

- Spectra Comp: 3 band Spectral Compression
- User Memories: 3 memory locations storing all front panel

## TC ELECTRONIC BH500

controls except Mute & Master Level

- Tuner: Bass Tuner, "On" when muted
- Tuning range: B0 (30.87Hz) to G4 (392.00Hz)
- Mute: Mutes speaker out, Phones out and Balanced out
- Master Level / Headphones Output: Studio quality headphone amp
- HP Out Impedance: 40 to 600 Ohm
- Mains supply: 100 - 120V~ or 220 - 240V~ 50/60Hz (65W @ 1/8 of Max. Output)
- Power rating: 500W (1000w Peak)
- Speaker output: Neutrik Speakon™
- Balanced output: Balanced XLR, Pre/Post Pre-amp
- Bal. Out Max.: +2dBu
- Bal. Out Optimal Load Impedance: 600 Ohm
- Rehearsal input: RCA, Left/Right input, fits to iPod ®
- Dimensions: 462 x 135 x 380 mm
- Weight: 13 kg
- Finish: Tolex covered, handcrafted wooden box

Prezzo : €345,00 IVA inclusa (€282,79 esclusa IVA)

---