

## DYNAUDIO BM12A



**DYNAUDIO**  
Professional

Cod.Art. : 11442

MONITOR ATTIVO 8"/1.1" 2 VIE 150W

Il BM 12A è un monitor analogico attivo a due vie con woofer da 8" e tweeter 1.1" a cupola morbida che sfrutta la tecnologia dei driver al neodimio proprietaria di Dynaudio Acoustics. Il BM 12A include filtri con profilo di equalizzazione commutabili per ottimizzare il posizionamento degli altoparlanti, così come i filtri passa-alto per l'uso con subwoofer, come ad esempio il Dynaudio Acoustics BM14S.

### Caratteristiche principali

- Neodymium 8" woofer
- Neodymium soft dome tweeter
- Integrated positioning filters (LF/MF/HF shelving/notch)
- 60/80Hz high-pass filter for subwoofer adaptation
- Balanced analog XLR input
- 50W/100W tweeter/woofer amplifier
- Input sensitivity switch (-10/+4dB range)
- Clip indicator LED
- Thermal amplifier protection
- ATTENZIONE: il prezzo è inteso per la cassa SINGOLA

### Specifiche tecniche

- System: Two-way Active Nearfield Monitor
- Frequency Response (+/- 3 dB): 38 Hz - 21 kHz
- Max SPL 1m, pair (IEC Short Term): 123 dB RMS
- Max SPL 2m, 5.1 (IEC Short Term): 124.5 dB RMS
- Input level for 85 dB SPL @1m (+4/-10): -18dBu RMS @ 0dB

## DYNAUDIO BM12A

setting

- Input level for max peak SPL (+4/-10): +12dBu RMS @ 0dB

setting

- Power consumption: Idle: 15 W / Max: 130 W

- Amplifier power: Tweeter: 50 W / Woofer: 100 W

- Resonance Frequency: 40 Hz

- Internal Cabinet Volume: 13.6 liters

- Bass Principle: Bass reflex

- Crossover Frequencies: 1500 Hz

- Crossover Slope: 6 dB/oct

- Tweeter: Esotec 28 mm/1.1" soft dome, rear chamber, Neodymium Magnetic. 4 mm die-cast alu front, Pure alu wire voice coil

- Woofer: 200 mm/8" Neodymium, One-piece molded poly-prop cone, 75 mm/3" kapton voice coil

- Weight: 12.1 kg / 26.6 lbs

- Dimensions (W x H x D): 234 x 370 x 327 mm / 9.2" x 14.6" x 12.9"

Prezzo : €965,00 IVA inclusa (~~€790,98 esclusa IVA~~)

**Prezzo in offerta : €898,00 IVA inclusa (€736,07 esclusa IVA)**