

## AKAI E2 Headrush Usato



Produttore : AKAI Professional  
Cod.Art. : 122056

### LOOPSTATION CON EFFETTI

L'Akai Professional E2 Headrush fornisce delay, simulazioni eco a nastro e un registratore loop in un unico pedale. L'Opzioni di ritardo selezionabile dall'utente consente il massimo controllo del segnale di uscita. Feedback in tempo reale e regolazione del guadagno così come echo rate. Headrush simula anche un eco a nastro

a 4-testine con il controllo di decadimento e la spaziatura tra le testine del nastro virtuale per creare ritardi multipli e complesse ripetizioni. Il segnale proveniente da ciascuna testina virtuale appare su una singola uscita per essere utilizzato con un mixer. La modalità LOOPING RECORDER permette di registrare e sovraincidere

layer e layer di suono in tempo reale, rendendo l'Headrush uno strumento incredibile nelle performance dal vivo. A seconda della modalità selezionata, il pedale sinistro controlla l'on/off e play/stop, mentre il pedale a destra imposta il tap delay o le opzioni di registrazione e sovraincisione. Il display LED indica quale effetto in uso e lampeggia a tempo con il tempo di ritardo selezionato.

### Caratteristiche

- 16-bit Digital Delay - Delay time from 0.5ms to an astonishing 23.8 seconds maximum
- Real-time delay control - sets delay time by tapping footswitch twice
- Tape Echo mode with four individual outputs for each head
- Looping Recorder with overdub mode - Powerful tool for solo performances
- Selectable Fixed or Adjustable Loop Level.

Specifiche  
tecniche

## AKAI E2 Headrush Usato

- Modes NORMAL DELAY, TAPE ECHO and LOOPING
- Resolution 16bit
- Sample rate Normal : 44.1kHz
- Extend: 29.4kHz
- Maximum time Delay: 23.8 seconds
- Tape Echo: 5.9 seconds
- Looping: 23.8 seconds, 11.9 seconds overdub [Normal]; 35.6 seconds, 17.8 seconds overdub [Extended]
- Controls LEVEL, HF DAMP, FEEDBACK, TIME COARSE/TIME, TIME FINE/HEAD GAP, RATIO
- Switches MODE SELECT, LOOP LEVEL, LOOP TIME, Footswitch x 2
- LEDs MODE x 3, EFFECT ON/OFF x1, TEMPO x1
- Connections Input: 1/4" jack. Input impedance 500kOhms or more
- Outputs: Mix, Effect/Head 1, Heads 2-4: 1/4" jack x 5, output impedance 1kOhms or less
- 9V DC in
- Options: AC adaptor (MP9-III )
- Dimensions: 140mm x 183.5mm x 65mm
- Weight: 1.15kg

Prezzo : €79,00 IVA inclusa (€79,00 esclusa IVA)

---