

MARKBASS Little Mark II



Cod.Art. : 2824

TESTATA PER BASSO SUPER LEGGERA 500W RMS

La Little Mark II è la nostra risposta alle richieste di una testata SUPER LEGGERA ma anche potente. Il connubio dei filtri VLE, VFP e l'equalizzatore grafico vi offrono un sound caldo e naturale, ottimo per gli strumenti acusticiQ
La Semplicissima Little Mark II è facile da usare e piena di risorse. 500W di potenza per un peso inferiore a 3kg

INPUTS

- INPUT impedance 500 Kohm, max. voltage 15 Vpp
- BALANCED INPUT (XLR) impedance 22 Kohm, max. voltage 25 Vpp
- EFFECT RETURN impedance 22 Kohm, max. voltage 25 Vpp

CONTROLS

- GAIN -80 dB to +23 dB range
- MASTER VOLUME
- LINE OUT level control on front panel
- GROUND LIFT switch on rear panel

EQUALIZATION

- LOW center frequency: 60 Hz; level: ± 16 dB
- LOW MID center frequency: 360 Hz, level: ± 16 dB
- HIGH MID center frequency: 800 Hz, level: ± 16 dB
- HIGH 5 kHz shelf, level: ± 16 dB
- VPF (Variable Pre-shape Filter) center frequency 380 Hz

MARKBASS Little Mark II

(cut)

- VLE (Vintage Loudspeaker Emulator) frequency range 250 Hz–20 kHz (cut)

OUTPUT

- LINE OUT balanced XLR, max. voltage 10 Vpp
- EFFECT SEND unbalanced, max. voltage 20 Vpp (pre-EQ)
- TUNER OUT unbalanced, max. voltage 25 Vpp
- SPEAKER OUT speakon, 1/4"

OTHER

- WEIGHT 6.39 lbs / 2.9 kg
- DEPTH 10.1 in. / 25.6 cm
- WIDTH 10.87 in. / 27.6 cm
- OUTPUT POWER 300W RMS @ 8 ohm, 500W RMS @ 4 ohm
- POWER REQUIREMENT 100/120V; 230V; 240V 50/60Hz

Prezzo : €549,00 IVA inclusa (€450,00 esclusa IVA)
