

## AUDIO TECHNICA AT3035



audio-technica

Cod.Art. : 3836

### MICROFONO A CONDENSATORE CARDIOIDE

The AT3035 is intended for use in professional applications where remote power is available. It requires 11V to 52V DC phantom power, which may be provided by a mixer or console, or by a separate, in-line source such as the Audio-Technica AT8801 singlechannel and CP8506 four-channel phantom power supplies. Output from the microphone's XLRM-type connector is low impedance (Lo-Z) balanced.

The signal appears across Pins 2 and 3; Pin 1 is ground (shield). Output phase is "Pin 2 hot" - positive acoustic pressure produces positive voltage at Pin 2. To avoid phase cancellation and poor sound, all mic cables must be wired consistently: Pin 1-to-Pin 1, etc. An integral 80 Hz hi-pass filter provides easy switching from a flat frequency response to a low-end roll-off. The high pass position reduces the microphone's sensitivity to popping in close vocal use. It also reduces the pickup of low-frequency ambient noise (such as traffic, air-handling systems, etc.), room reverberation and mechanically-coupled vibrations. In use, secure the cable to the mic stand or boom, leaving a slack loop at the mic. This will ensure the most effective shock isolation and reduce the possibility of accidentally pulling the microphone out of its mount. Avoid leaving the microphone in the open sun or in areas where temperatures exceed 110° F (43° C) for extended periods. Extremely high humidity should also be avoided.

### Caratteristiche

- Large diaphragm for exceptional detail and low noise
- High SPL handling and wide dynamic range provide unmatched

## AUDIO TECHNICA AT3035

### versatility

- Custom shock mount provides superior isolation
- Switchable 80 Hz hi-pass filter and 10 dB pad
- Cardioid polar pattern reduces pickup of sounds from the sides and rear, improving isolation of desired sound source

### Specifiche tecniche

- ELEMENT Fixed-charge back plate permanently polarized condenser
- POLAR PATTERN Cardioid
- FREQUENCY RESPONSE 20-20,000 Hz
- LOW FREQUENCY ROLL-OFF 80 Hz, 12 dB/octave
- OPEN CIRCUIT SENSITIVITY -32 dB (25.1 mV) re 1V at 1 Pa\*
- IMPEDANCE 250 ohms
- MAXIMUM INPUT SOUND LEVEL 148 dB SPL, 1 kHz at 1% T.H.D.;
- 158 dB SPL, with 10 dB pad (nominal)
- NOISE 12 dB SPL
- DYNAMIC RANGE (typical) 136 dB, 1 kHz at Max SPL
- SIGNAL-TO-NOISE RATIO 82 dB, 1 kHz at 1 Pa\*
- PHANTOM POWER 11-52V DC, 3 mA typical
- SWITCHES Flat, roll-off; 10 dB pad (nominal)
- WEIGHT (less accessories) 13.8 oz (390 g)
- DIMENSIONS 6.69" (170.0 mm) long, 2.05" (52.0 mm) maximum body diameter
- OUTPUT CONNECTOR Integral 3-pin XLRM-type
- ACCESSORIES FURNISHED Shock mount for 5/8"-27 threaded stands; soft protective pouch

Prezzo : €189,00 IVA inclusa (€154,92 esclusa IVA)