

AVID Digi 003 Factory Bundle + ProTools LE 8



Cod.Art. : 5056

INTERFACCIA AUDIO FIREWIRE + SUPERFICIE DI CONTROLLO MIDI

Grazie alla sua vastissima gamma d'opzioni I/O audio e MIDI, risoluzione audio ad alta definizione, la creatività e la velocità peculiari del software Pro Tools - standard di riferimento del settore - la connessione FireWire nonché il vasto ed incredibilmente completo pacchetto di potente software allegato gratis, il nuovo 003 Factory vi permette di ottenere all'interno del vostro personal o project studio una produzione audio con gli stessi alti livelli qualitativi di una struttura commerciale. Con la superficie di controllo integrata di 003 Factory, inoltre, è possibile avere controllo diretto di tutte le sessioni Pro Tools LE ed approfittare del gran numero di opzioni I/O per il collegamento ed il monitoraggio di tutta la strumentazione dello studio. Le sue dimensioni contenute donano a tutti gli utenti la libertà di poter portare un sistema Pro Tools professionale ovunque ci sia bisogno della loro perizia e creatività o dove li porta l'ispirazione. Inoltre, con i più di 80 potenti plug-in, strumenti virtuali, applicazioni compatibili e servizi di promozione artistica inclusi, gli operatori potranno disporre di tutto ciò di cui hanno bisogno (e anche di più) per la composizione, la registrazione, l'editing, il mixaggio e il mastering di audio per progetti di post produzione musicale a computer. Con risultati professionali garantiti.

Caratteristiche

Mic Inputs

- Connector: Four balanced XLR jacks
- Mic Phantom Power: 48V
- Equivalent Input Noise: -129 dBu
- Frequency Response: +/- 0.1 dB, 20 Hz - 20 kHz
- Dynamic Range: 105 dB / 107 dB A-weighted

AVID Digi 003 Factory Bundle + ProTools LE 8

- THD + N: 0.0007% (-103 dB)
 - Mic EIN: -129 dBu
 - Input Sensitivity: +2.2 dBu
 - Input Impedance: 2K Ohm
- Line Outputs (1-8)
- Connector: Eight impedance balanced 1/4" jacks
 - Frequency Response: +/- 0.5 dB, 20 Hz - 20 kHz
 - Dynamic Range: 110 dB / 113 dB A-weighted
 - THD + N: 0.0007% (-103 dB)
 - Output Sensitivity: +18 dBu
- Line Inputs
- Connector: Four balanced 1/4" jacks
 - Frequency Response: +/- 0.1 dB, 20 Hz - 20 kHz
 - Dynamic Range: 111 dB / 113 dB A-weighted
 - THD + N: 0.0007% (-103 dB)
 - Input Sensitivity: +17.38 dBu
 - Input Impedance: 22K Ohm
- Monitor Outputs (Main & Alt)
- Connector: Two impedance balanced 1/4" jacks
 - Frequency Response: +/- 0.5 dB, 20 Hz - 20 kHz
 - Dynamic Range: 110 dB / 112 dB A-weighted
 - THD + N: 0.0008% (-102 dB)
 - Output Sensitivity: +18 dBu
- DI Inputs
- Connector: Four unbalanced 1/4" jacks
 - Frequency Response: +/- 0.1 dB, 20 Hz - 20 kHz
 - Dynamic Range: 104 dB / 106 dB A-weighted
 - THD + N: 0.0008% (-102 dB) - Balanced input
 - Input Sensitivity: +17.16 dBu
 - Input Impedance: >300K Ohm
- Headphone Outputs
- Connector: Two unbalanced 1/4" jacks
 - Frequency Response: +/- 0.5 dB, 20 Hz - 20 kHz
 - THD + N: 0.0009% (-101 dB)
 - Dynamic Range: 110 dB / 112 dB A-weighted
 - Output Sensitivity: +23 dBu
- Aux Inputs
- Connector: Two balanced 1/4" jacks
 - Frequency Response: +/- 0.1 dB, 20 Hz - 20 kHz
 - Dynamic Range: 111 dB / 113 dB A-weighted

AVID Digi 003 Factory Bundle + ProTools LE 8

- THD + N: 0.00055% (-105 dB)
 - Input Sensitivity: +17.16 dBu
 - Input Impedance: 10K Ohm
- Digital Specifications
- Supported Sample Rates: 44.1, 48, 88.2, 96 kHz
 - Maximum Word Length: 24-bit
 - S/PDIF: 2-channel optical or RCA jack pair
 - Digital Optical: TOSLINK (ADAT, max 48 kHz sample rate)
 - Word Clock: Two BNC jacks
 - Host Connection: Two IEEE-1394a (FireWire) ports (6-pin-to-6-pin FireWire cable included)
 - MIDI: 5-pin MIDI DIN connectors - one input, two outputs
- Size / Weight / Power
- Height: 5.125 inches / 13 cm
 - Width: 19.25 inches / 48.90 cm
 - Depth: 19.25 inches / 48.90 cm (including all connectors)
 - Weight: 16.1 lbs / 7.3 kg
 - Power Requirements: 100 - 240V, 50 - 60 Hz A/C (power cable included)

Prezzo : €2.149,00 IVA inclusa (€1.761,48 esclusa IVA)

Prezzo in offerta : €888,00 IVA inclusa (€727,87 esclusa IVA)