

ROLAND CD2e SD/CD Recorder



Produttore : Roland

Cod.Art. : 6489

REGISTRATORE CD-SD PROFESSIONALE

Cattura il suono, ascolta, e crea il tuo CD in modo facile e veloce. CD-2e è il recorder più facile da usare al mondo. Registrare, ascoltare e creare un CD audio... tutte queste possibilità in un recorder leggero, sottile e dal design accattivante.

Caratteristiche principali

- Estrema facilità d'utilizzo
- Design tutto in uno con microfono e speaker incorporati
- Possibilità di utilizzo con SD/SDHC card removibile per espandere il tempo di registrazione e facilitare le procedure di editing.
- Possibilità di utilizzo con batterie stilo
- Funzioni utili per la didattica musicale
- Display con possibilità multi-lingue

Specifiche tecniche

RECORDER PART

- Tracks: 2 (Stereo)
- Sampling Rate: 44.1 kHz
- Signal Processing: AD/DA conversion: 24 bits
- Recording Mode: SD Memory Card: WAV (44.1 kHz, 16 bits), CD-R, CD-RW: Audio CD
- Recording Media: SD Memory Card (supports 64 MB–8 GB, SDHC

format compatible), CD-R, CD-RW

- Recording Time: CD-R or CD-RW disc (650 MB = 74 min; 700 MB = 80 min) SD Memory Card: up to 763min with 8GB SD. *Each recording time is an approximate estimate including some errors.

ROLAND CD2e SD/CD Recorder

- Recording Songs: Up to 99 songs on a single SD Memory Card, CD-R, or CD-RW

INPUT/OUTPUT

- Audio Input: Internal Stereo Microphone; EXT MIC Input L/MONO, R Jack: 1/4 inch phone type; LINE Input Jacks (L, R): RCA phono type

- Audio Output: Internal Stereo Speaker; PHONES Jack: Stereo miniature phone type; Line Out Jack: Stereo miniature phone type

- Frequency Response: 20 Hz–20 kHz (+0dB/-2dB)

- Nominal Input Level (variable): EXT MIC Input L/MONO, R Jack: -51– -14 dBu (maximum -2 dBu); LINE Input Jacks (L, R): -24– 0 dBu (maximum +12 dBu)

- Nominal Output Level: Line Output Jack: -10 dBu (maximum +2 dBu)

- Input Impedance: EXT MIC Input L/MONO, R Jack: 20 k ohms; Line Input Jacks (L, R): 9 k ohms

- Output Impedance: Line Output Jack: 1 k ohms; Phones Jack: 22 ohms

- Recommended Load Impedance: Line Output Jack: 10 k ohms or greater; Phones Jack: 32 ohms

OTHERS

- Display: 16 characters, two lines (backlit LCD)

- Dimensions: 267 (W) x 183 (D) x 46 (H) mm

- Weight: 1.1 kg

- Power Supply: AC Adaptor (PSB-1U), Dry battery LR6 (AA) type (alkaline) x 6

- Expected battery life under continuous use: approx. 6 hours with alkaline dry cell batteries * The time may vary according to usage conditions, batteries used, and type of SD memory card used.

- Current Draw: 540 mA

Prezzo : €599,00 IVA inclusa (~~€490,98 esclusa IVA~~)

Prezzo in offerta : €349,00 IVA inclusa (€286,07 esclusa IVA)