

DYNAUDIO BM6A MKII



DYNAUDIO
Professional

Cod.Art. : 8356

MONITOR ATTIVIO 6.9"/1.1" 2 VIE 150W

This two-way active analog nearfield monitor with a 6.9" woofer and a 1.1" soft dome tweeter delivers distinctive Dynaudio clarity and accuracy, exposing every audible detail for the critical and demanding engineer. Onboard LF/MF/HF placement filters, as well as subwoofer high-pass filters allow the monitor to easily adapt to any environment.

Specifiche tecniche

- System: Two-way Active Nearfield Monitor
- Frequency Response: (+/- 3 dB) 40Hz - 21kHz
- Max SPL 1m, pair: (IEC Long Term) 115 dB peak
- Max SPL 2m, 5.1: (IEC Long Term) 115 dB peak
- Input level for 85 dB SPL @ 1m (+4/-10): -14dBu RMS @ 0dB setting
- Input level for max peak SPL (+4/-10): +9dBu Peak @ 0dB setting
- Power consumption Idle: 15 W / Max: 130 W
- Amplifier power Tweeter: 50 W / Woofer: 100 W
- Resonance Frequency: 37 Hz
- Internal Cabinet Volume: 11.7 liters
- Bass Principle: Bass reflex
- Crossover Frequencies: 1500 Hz
- Crossover Slope: 6 dB/oct
- Tweeter: Esotec 28 mm/1.1" soft dome, rear chamber, Magnetic fluid. 4 mm die-cast alu front, Pure alu wire voice coil
- Woofer: 175 mm/6.9", One-piece molded poly-prop cone, 75 mm/3" pure alu voice coil
- Weight: 10.5 kg / 23.12 lbs

Monitor da Studio > Monitor da Studio Attivi da 6" a 10"

DYNAUDIO BM6A MKII

- Dimensions: (WxHxL) 203 x 335 x 327 mm / 8" x 13.2" x 12.9"

- ATTENZIONE: il prezzo è inteso per la cassa SINGOLA

Prezzo : €695,00 IVA inclusa (~~€569,67 esclusa IVA~~)

Prezzo in offerta : €598,00 IVA inclusa (€490,16 esclusa IVA)