

GENELEC 8020B



GENELEC®

Cod.Art. : 8612

MONITOR DA STUDIO BIAMPLIFICATO 40W

The small Genelec 8020B (Height with Iso-Pod 242 mm, Width 151 mm and Depth 142 mm) has been designed for monitoring in difficult listening environments, particularly those compromised by lack of space. However, size is no handicap to performance as the 8020A two-way active monitoring system incorporates Genelec's acoustic design innovations to minimise all forms of distortion. The 8020B has a die-cast aluminium Minimum Diffraction Enclosure (MDE™), which features relatively large internal volumes; softly curved edges and outstanding mechanical strength. As a result, the imaging accuracy and low frequency extension with such a compact enclosure are truly astounding. The 8020B also incorporates the advanced Directivity Control Waveguide (DCW™), which provides an amazingly smooth on and off axis response; while the long, curved reflex port ends in a wide flare for excellent bass articulation

Caratteristiche principali

- Input format: Analog
- SPL
- Maximum short time sine wave acoustic output at 1 m on axis in half space, averaged from 100 Hz to 3 kHz; 95 dB SPL
- Maximum peak acoustic output per pair with music material; 105 dB SPL @ 1m
- Drivers
- Bass 105 mm (4")
- Treble 19 mm (3/4") metal dome
- Crossover frequencies 3 kHz

Monitor da Studio > Monitor da Studio Attivi da 3" a 5"

GENELEC 8020B

- Free field frequency response 66 Hz - 20 kHz (± 2.5 dB)

Amplifier Power/Ch

- Bass 20 W

- Treble 20 W

Varie

- Colore: antracite

- Dimensioni: H226 x 151 x 142mm

- Dimensioni: H242 x 151 x 142mm (con Iso-Pod)

- Peso: 3.7 kg (8.1 lb)

ATTENZIONE: il prezzo è inteso per la cassa SINGOLA

Prezzo : €395,00 IVA inclusa (~~€323,77 esclusa IVA~~)

Prezzo in offerta : €299,00 IVA inclusa (€245,08 esclusa IVA)