

APOGEE Symphony I/O Chassis



Cod.Art. : 9977

INTERFACCIA AUDIO PROFESSIONALE

Interfaccia audio professionale (solo unità base) equipaggiata con 2 slot per moduli I/O, connettori Main e Thru (per il collegamento con schede Symphony 64 PCIe, Symphony Mobile e Pro Tools HD), USB,

Ethernet, Word Clock In e Loop In, Word Clock Out e Loop Out, interruttore per la terminazione del Word Clock, 2 uscite per cuffia con jack da 1/4", 2 manopole di controllo multifunzione, ampio display con indicatori di livello, alimentazione 110-240/50-60Hz, dimensioni 2 unità rack, compatibile con Mac OSX

10.5.8 o superiore.

*I moduli I/O non sono inclusi

Specifiche

tecniche

Analog to Digital:

- THD+N: -113dB @ 20dBu (0.00024%)
- Dynamic range: 120dB A weighted
- Maximum input levels:
- +4dB setting - 24dBu
- -10dB setting - +6dBV
- Variable gain setting - 25dB of gain
- Frequency response at 44.1kHz 1-20,000 Hz (+/- 0.05dB)
- Input impedance: 10K

Digital to Analog:

- THD+N: -117dB @ 20dBu (0.00014%)
- Dynamic Range: 129dB A weighted
- Max output levels - ∞ to +24dBu
- Frequency response at 44.1 kHz: dc to 20kHz (+/-

APOGEE Symphony I/O Chassis

0.05dB)

- Output impedance: 25 Ohm
- Outputs are balanced through Apogee's proprietary Perfect Symmetry Circuitry (PSC)

Headphones:

- THD+N: -105dB @19dBu
 - Dynamic Range: 119db A weighted
 - Output impedance: 30 Ohm
- Operating System:
- Mac OS only 10.5.8 and above

Package Contents:

- Symphony I/O Interface
- USB Cable
- Power Cable
- Rack Ears and Bolts
- Quick Start Guide

Symphony I/O Dimensions (cm):

- 45 (48.26 with Rack Ears) x 29.2 x 8.9 (10.2 with feet installed)

Prezzo : €1.389,00 IVA inclusa (€1.138,52 esclusa IVA)
